

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

**AN ORDINANCE REPEALING THE DELANO FLOODPLAIN ORDINANCE O-06-08 AND ADOPTING AN
UPDATED FLOODPLAIN ODINANCE CITY WITHIN THE CITY OF DELANO**

THE DELANO CITY COUNCIL DOES ORDAIN

Section 1. The Delano Floodplain Ordinance O-06-08 is repealed in its entirety.

Section 2. The Delano City Code is hereby amended to include a floodplain ordinance to read as follows:

SECTION 1.0 STATUTORY AUTHORIZATION AND PURPOSE

1.1 Statutory Authorization. This floodplain ordinance is adopted pursuant to the authorization and policies contained in Minnesota Statutes, Chapter 103F; Minnesota Rules, parts 6120.5000 – 6120.6200; the rules and regulations of the National Flood Insurance Program (NFIP) in 44 CFR § 59 to 78; and the planning and zoning enabling legislation in Minnesota Statutes, Chapter 462.

1.2 Purpose

1.21 This ordinance regulates development in the flood hazard areas of Delano Minnesota. These flood hazard areas are subject to periodic inundation, which may result in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base. It is the purpose of this ordinance to promote public health, safety, and general welfare by minimizing these losses and disruptions.

1.22 This ordinance is adopted in the public interest to promote sound land use practices, and floodplains are a land resource to be developed in a manner which will result in minimum loss of life and threat to health, and reduction of private and public economic loss caused by flooding.

1.23 This ordinance is adopted to maintain eligibility in the National Flood Insurance Program.

1.24 This ordinance is also intended to preserve the natural characteristics and functions of watercourses and floodplains in order to moderate flood and stormwater impacts, improve water quality, reduce soil erosion, protect aquatic and riparian habitat, provide recreational opportunities, provide aesthetic benefits and enhance community and economic development.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

1.3 Abrogation and Greater Restrictions. It is not intended by this ordinance to repeal, abrogate, or impair any existing easements, covenants, or other private agreements. The standards in this ordinance take precedence over any less restrictive, conflicting local laws, ordinances, or codes. All other ordinances inconsistent with this ordinance are hereby repealed to the extent of the inconsistency only.

1.4 Warning and Disclaimer of Liability. This ordinance does not imply that areas outside the floodplain districts or land uses permitted within such districts will be free from flooding or flood damages. Not all flood risk is mapped. Larger floods do occur, and the flood height may be increased by man-made or natural causes, such as ice jams or bridge openings restricted by debris. This ordinance does not create liability on the part of Delano Minnesota or its officers or employees for any flood damages that result from reliance on this ordinance, or any administrative decision lawfully made hereunder.

1.5 Severability. If any section, clause, provision, or portion of this ordinance is adjudged unconstitutional or invalid by a court of law, the remainder of this ordinance shall not be affected and shall remain in full force.

SECTION 2.0 DEFINITIONS

2.1 Definitions. The following definitions shall be applicable exclusively within the Floodplain overlay districts. Unless specifically defined, words or phrases used in this ordinance must be interpreted according to common usage and so as to give the floodplain ordinance its most reasonable application.

2.111 Accessory Structure. A structure, as defined in this ordinance, that is on the same parcel of property as, and is incidental to, the principal structure or use; an accessory structure specifically excludes structures used for human habitation.

2.112 Base Flood. The flood having a one-percent chance of being equaled or exceeded in any given year. “Base flood” is synonymous with the term “regional flood” used in Minnesota Rules, part 6120.5000.

2.113 Base Flood Elevation (BFE). The elevation of the base flood, regional flood (100 year flood event), or one-percent annual chance flood. The term “base flood elevation” is used in the flood insurance study.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

2.114 Basement. Any area of a structure, including crawl spaces, having its floor subgrade (below ground level) on all sides, regardless of the depth of excavation below ground level.

2.115 Building. See *Structure*.

2.116 Channel. A natural or artificial depression of perceptible extent, with definite bed and banks to confine and conduct flowing water either continuously or periodically.

2.117 Conditional Use. A land use or development that would not be appropriate generally but may be allowed with appropriate restrictions upon a finding that certain conditions as detailed in the zoning ordinance exist, the use or development conforms to the comprehensive land use plan of the community, and the use is compatible with the existing neighborhood.

2.118 Critical Facilities. Buildings and structures that contain essential facilities and services necessary for emergency response and recovery, or that pose a substantial risk to the public in the event of failure, disruption of function, or damage by flooding. Specifically, this includes facilities identified as Flood Design Class 4 in *ASCE 24-14, Flood Resistant Design and Construction*, as amended. Examples include ~~health care facilities~~, facilities required for emergency response, power generating stations, communications towers, or electrical substations.

2.119 Development. Any man-made change to improved or unimproved real estate, including, but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment or materials.

2.120 Equal Degree of Encroachment. A method of determining the location of floodway boundaries so that floodplain lands on both sides of a stream are capable of conveying a proportionate share of flood flows.

2.121 FEMA. Federal Emergency Management Agency.

2.123 Flood. A temporary rise in the stream flow or water surface elevation from any source that results in the inundation of normally dry land areas.

2.124 Flood Fringe. The portion of the one-percent annual chance (100 year flood event) floodplain that is located outside of the floodway.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

2.125 Flood Insurance Rate Map (FIRM). An official map on which the Federal Insurance Administrator has delineated both the special flood hazard areas and the risk premium zones applicable to the community. A FIRM that has been made available digitally is called a Digital Flood Insurance Rate Map (DFIRM).

2.126 Flood Insurance Study (FIS). The study referenced in Section 3.2, which is an examination, evaluation and determination of flood hazards, and if appropriate, corresponding surface elevations, or an examination, evaluation, and determination of mudslide (i.e. mudflow) and/or flood-related erosion hazards.

2.127 Floodplain. The beds, channel and the areas adjoining a wetland, lake or watercourse, or other source which have been or hereafter may be inundated by the base flood.

2.128 Floodproofing. A combination of structural and non-structural additions, changes, or adjustments to properties and structures subject to flooding, primarily for the reduction or elimination of flood damages.

2.129 Floodway. The bed of a wetland or lake and the channel of a watercourse and those portions of the adjoining floodplain which must be reserved to carry or store the base flood discharge without cumulatively increasing the water surface elevation more than one-half foot.

2.130 General Floodplain. Those floodplains designated on the Flood Insurance Rate Maps referenced in Section 3.2, but that do not have a delineated floodway.

2.131 Lowest Floor. The lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage in an area other than a basement area, is not considered a building's lowest floor; provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of 44 CFR § 60.3.

2.132 Manufactured Home. A structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when attached to the required utilities. The term "manufactured home" does not include the term "recreational vehicle."

2.133 New Construction. Structures for which the start of construction commenced on or after the effective date of an adopted floodplain management regulation and includes any subsequent improvements to such structures.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

2.134 Principal Structure. The main building or other structure on a lot that is utilized for the property's principal use.

2.135 Reach. A hydraulic engineering term to describe a longitudinal segment of a stream or river influenced by a natural or man-made obstruction. In an urban area, the segment of a stream or river between two consecutive bridge crossings would most typically constitute a reach.

2.136 Recreational Vehicle. A vehicle that is built on a single chassis, is 400 square feet or less when measured at the largest horizontal projection, is designed to be self-propelled or permanently towable by a light duty truck and is designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use. Those vehicles not meeting this definition shall be considered a structure for the purposes of this ordinance. For the purposes of this ordinance, the term recreational vehicle is synonymous with the term "travel trailer/travel vehicle."

2.137 Regulatory Flood Protection Elevation (RFPE). An elevation that is one foot above the elevation of the base flood plus any increases in the water surface elevation caused by encroachments on the floodplain that result from designation of a floodway. These increases in water surface elevations are typically identified in the Floodway Data Tables, found in the Flood Insurance Study.

2.138 Repetitive Loss. Flood related damages sustained by a structure on two separate occasions during a ten-year period for which the cost of repairs at the time of each such flood event on the average equals or exceeds 25% of the market value of the structure before the damage occurred.

2.139 Stage Increase. Any increase in the water surface elevation during the one-percent annual chance flood caused by encroachments on the floodplain.

2.140 Start of Construction. Includes substantial improvement, and means the date the permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, foundations, or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

2.141 Structure. A roofed building, including a gas or liquid storage tank, that is principally above ground, as well as a manufactured home. Recreational vehicles not considered travel ready, as detailed in Section 11.22, shall also be considered a structure for the purposes of this ordinance.

2.144 Subdivision. Land that has been divided for the purpose of sale, rent, or lease, including planned unit developments.

2.145 Substantial Damage. Damage of any origin sustained by a structure where the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

2.146 Substantial Improvement. Any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures that have incurred "substantial damage," regardless of the actual repair work performed. The term does not, however, include either: A. Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions, or B. Any alteration of a "historic structure," provided that the alteration will not preclude the structure's continued designation as a "historic structure." For the purpose of this ordinance, "historic structure" is defined in 44 CFR § 59.1.

2.147 Variance. "Variance" means the same as that defined in 44 CFR § 59.1 and Minnesota Statutes, *Section 462.357, Subd. 6(2)*.

2.148 Watercourse. A channel in which a flow of water occurs either continuously or intermittently in a definitive direction. The term applies to either natural or artificially constructed channels.

SECTION 3.0 JURISDICTION AND DISTRICTS

3.1 Lands to Which Ordinance Applies. This ordinance applies to all lands within the jurisdiction of Delano Minnesota within the boundaries of the Floodway, Flood Fringe and General Floodplain Districts.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

3.11 The Floodway, Flood Fringe or General Floodplain Districts are overlay districts. The standards imposed in the overlay districts are in addition to any other requirements. In case of a conflict, the more restrictive standards will apply.

3.12 Where a conflict exists between the floodplain limits illustrated on the official floodplain maps and actual field conditions (as illustrated in Figure 1), the Base Flood Elevation (BFE) shall be the governing factor in locating the outer boundaries of the one-percent annual chance floodplain.

Figure 1: The mapped floodplain may not always align with on-the-ground contour elevations.



3.13 Persons contesting the location of the district boundaries will be given a reasonable opportunity to present their case to the Board of Adjustment] and to submit technical evidence.

3.2 Incorporation of Maps by Reference. The following maps together with all attached material are hereby adopted by reference and declared to be a part of the official zoning map and this ordinance. The attached material includes the Flood Insurance Study for Wright County, Minnesota, and Incorporated Areas, dated 06/20/2024 and the Flood Insurance Rate map panels 27171C0505D, 27171C0510D, 27171C0515D, 27171C0516D, 27171C0517D, 27171C0518D, and 27171C0519D, dated 06/20/2024, all prepared by the Federal Emergency Management Agency. These materials are on file at Delano, Minnesota City Hall.

3.3 Districts

3.31 Floodway District. Those areas within Zones AE delineated within floodway areas as shown on the Flood Insurance Rate Maps referenced in Section 3.2.

3.32 FF-1 Flood Fringe District One. Those areas within Zones AE located outside of the delineated floodway, as shown on the Flood Insurance Rate Maps referenced in Section 3.2.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

3.33 FF-2 Flood Fringe District Two. The Flood Fringe District Two shall include those areas designated as floodway fringe and located within the City of Delano's Long Range Land Use Plan and annexed into the City after January 31, 2005. The Flood Fringe shall constitute those areas shown on the Flood Insurance Rate Map as adopted in Section 3.2 as being within Zone AE but being located outside the floodway.

3.34 General Floodplain District. Those areas within Zone A and AE areas that do not have a floodway delineated as shown on the Flood Insurance Rate Maps referenced in Section 3.2.

3.4 Annexations. The Flood Insurance Rate Map panels referenced in Section 3.2 may include floodplain areas that lie outside of the corporate boundaries of the City of Delano at the time of adoption of this ordinance. If any of these floodplain land areas are annexed into the City of Delano after the date of adoption of this ordinance, the newly annexed floodplain lands will be subject to the FF-2 Flood Fringe Two District provisions of this ordinance immediately upon the date of annexation. Annexations into panels not referenced in Section 3.2 require ordinance amendment in accordance with Section 15.0.

3.5 Municipal Boundary Adjustments & Townships. The Flood Insurance Rate Map panels referenced in Section 3.2 apply countywide. If at any point any lands come under the jurisdiction of another local government, the following shall apply:

3.51 City adjustments of corporate boundaries, including but not limited to annexations and detachments, shall shift floodplain administrative authority of all affected lands immediately upon the date of the boundary adjustment occurring. Cities retain jurisdiction for all incorporated lands, and the County retains jurisdiction under this ordinance on all unincorporated lands.

SECTION 4.0 REQUIREMENTS FOR ALL FLOODPLAIN DISTRICTS

4.1 Permit Required. A permit must be obtained from the Zoning Administrator to verify compliance with all applicable standards outlined in this ordinance prior to the following uses or activities:

4.11 The erection, addition, modification, rehabilitation, repair, or alteration of any building, structure, or portion thereof. Normal maintenance requires a permit to determine if such work, either separately or in conjunction with other planned work, constitutes a substantial improvement, as specified in Section 13.13.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

4.12 The construction of a fence, pool, deck, or placement of anything that may cause a potential obstruction. Farm fences, as defined in Section 2.0 of this ordinance, are not considered to be an obstruction, and as such, do not require a permit.

4.13 The change or expansion of a nonconforming use.

4.14 The repair of a structure that has been damaged by flood, fire, tornado, or any other source.

4.15 The placement of fill, excavation, utilities, on-site sewage treatment systems, or other service facilities.

4.16 The storage of materials or equipment, in conformance with Section 4.32.

4.17 Relocation or alteration of a watercourse (including stabilization projects or the construction of new or replacement dams, culverts and bridges). A local permit is not required if a public waters work permit has been obtained from the Department of Natural Resources, unless a significant area above the ordinary high water level is also to be disturbed.

4.18 Any other type of "development," as defined in Section 2.0 of this ordinance.

4.2 No Permit Required. Certain uses or activities may be exempt from obtaining a permit, such as planting a garden, farming, or other obviously insignificant activities such as putting up a mailbox or flagpole. The continuation of existing uses, when the associated activities do not encroach further on the regulatory floodplain or trigger associated standards in this ordinance, do not require a permit.

4.3 Minimum Development Standards

4.31 All development must:

- A. Be designed (or modified) and adequately anchored to prevent flotation, collapse, or lateral movement resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
- B. Be constructed with materials and equipment resistant to flood damage.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

- C. Be constructed by methods and practices that minimize flood damage.
- D. Be constructed with heating, ventilation, duct work, and air conditioning equipment and other service facilities elevated at least up to the Regulatory Flood Protection Elevation (RFPE). Water, sewage, electrical, and other utility lines below the RFPE shall be constructed so as to prevent water from entering or accumulating within them during conditions of flooding.
- E. Be reasonably safe from flooding and consistent with the need to minimize flood damage.
- F. Be assured to provide adequate drainage to reduce exposure to flood hazards.
- G. Not be detrimental to uses in adjoining areas.
- H. Not adversely affect the efficiency or restrict the flood carrying capacity of the channel and adjoining floodplain of any tributary watercourse or drainage system.
- I. Ensure that any fill or other materials are protected from erosion, discharge, and sediment entering surface waters by the use of vegetative cover or other methods as soon as possible.

4.32 Materials that, in time of flooding, are buoyant, flammable, explosive, or could be injurious to human, animal, or plant life shall be stored at or above the Regulatory Flood Protection Elevation (RFPE), floodproofed, or protected by other measures as approved by the Zoning Administrator. Storage of materials likely to cause pollution of the waters, such as sewage; sand; rock; wrecked and discarded equipment; dredged spoil; municipal, agricultural or industrial waste; and other wastes as further defined in Minnesota Statutes, Section 115.01, are prohibited unless adequate safeguards approved by the Minnesota Pollution Control Agency are provided. For projects not requiring approvals by the Minnesota Pollution Control Agency, adequate safeguards must be approved by the Zoning Administrator prior to issuance of a permit.

4.33 Critical facilities shall be located so that the lowest floor is not less than two feet above the Base Flood Elevation (BFE), or the 0.2% annual chance flood elevation, whichever is higher.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

| Table 1. Summary of Permitting Requirements for Structures Structure Type | Floodway | Flood Fringe One | Flood Fringe Two | Standards* *Note - many of these standards are cross-referenced |
|----------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------|-------------------------|------------------------------------------------------------------------|
| | | FF-1 | FF-2 | |
| Accessory Structures – on fill | Only specific uses and types allowed – with CUP | Allowed with Permit Per section 6.23.D(2) | Prohibited | 6.23.D(2) |
| Accessory Structures – Alt. Elevation Methods | Only specific uses and types allowed – with CUP | Allowed with Permit Per section 6.23.D(3) | Prohibited | 6.23.D(3) |
| Accessory Structures – Wet Floodproofing | Only specific uses and types allowed – with CUP | Allowed with Permit Per section 6.23.D(1) | Prohibited | 6.23.D(1) |
| Accessory Structures – Dry (watertight) Floodproofing | Only specific uses and types allowed – with CUP | Allowed with Permit Per section 6.23.D(4) | Prohibited | 6.23.D(4) |
| Residential – on fill | Not allowed | Allowed with Permit Per section 6.21.A | Prohibited | 6.21.A |
| Residential – Alt. Elevation Methods | Not allowed | Allowed with CUP Per section 6.41 | Prohibited | 6.41 |
| Residential – Dry (watertight) Floodproofing and/or Basement | Not allowed | Not allowed | Prohibited | N/A |
| Construction below RFPE | | | | |
| Non-Residential – on fill | Not allowed | Allowed with Permit Per Section 6.22.A | Prohibited | 6.22.A |
| Non-Residential – Alt. Elevation Methods | Not allowed | Allowed with Permit Per section 6.22.B | Prohibited | 6.22.B |
| Non-Residential – Dry (watertight) Floodproofing and/or Basement | Not allowed | Allowed with Permit Per Section 6.22.C | Prohibited | 6.22.C |
| Construction below RFPE | | | | |

SECTION 5.0 FLOODWAY DISTRICT

5.1 Permitted Uses in Floodway. Development allowed in the floodway district is limited to that which has low flood damage potential and will not obstruct flood flows, increase velocities, or increase the water surface elevations of the one-percent annual chance flood. The following uses and activities may be allowed with a permit, subject to the standards in Section 5.2:

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

5.11 Agricultural uses, recreational uses, parking lots, loading areas, airport landing strips, water control structures, navigational facilities, as well as public open space uses.

5.12 Roads, driveways, railroads, trails, bridges, and culverts.

5.13 Public utility facilities and water-oriented industries which must be in or adjacent to watercourses.

5.14 Grading, filling, land alterations, and shoreline stabilization projects.

5.15 No structures, as defined in Section 2.0, are allowed in the Floodway District, except structures accessory to the uses detailed in Sections 5.11 and 5.31, which require a CUP under Section 5.32.

5.16 Levees or dikes intended to protect agricultural crops, provided the top of the dike does not exceed the 10-percent annual chance flood event.

5.2 Standards for Permitted Uses in Floodway. In addition to the applicable standards detailed in Section 4.0:

5.21 The applicant must demonstrate that the development will not result in any of the following during the one-percent annual chance flood: cause a stage increase of 0.00 feet or greater, obstruct flood flows, or increase velocities. This shall be demonstrated through hydrologic and hydraulic analysis performed by a professional engineer or using other standard engineering practices (e.g. projects that restore the site to the previous cross-sectional area). This is commonly documented through a “no-rise certification.”

5.22 Any development that would result in a stage increases greater than 0.00 feet may only be allowed with a permit if the applicant has applied for and received approval for a Conditional Letter of Map Revision (CLOMR) in accordance with 44 CFR § 65.12. Map revisions must follow the procedures in Sections 12.15 and 15.0.

5.23 Any development resulting in decreases to the water surface elevation of the base flood identified in the Flood Insurance Study requires a Letter of Map Revision (LOMR) following the procedures in Sections 12.15 and 15.0.

5.24 Any development in the beds of public waters that will change the course, current or cross section is required to obtain a public waters work permit in accordance with Minnesota Statutes, section 103G.245 or a utility crossing license in accordance with Minnesota Statutes, section 84.415, from the Department of Natural Resources, or demonstrate that no permit is required, before applying for a local permit.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

5.25 Any facility used by employees, or the general public must be designed with a flood warning system acceptable to the Zoning Administrator that provides adequate time for evacuation or be designed to ensure that within the area inundated during the base flood event, the depth (in feet) multiplied by the velocity (in feet per second) is less than four.

5.26 Fill and other land alteration activities must offer minimal obstruction to the flow of flood waters and be protected from erosion and sediment entering surface waters by the use of vegetative cover, riprap or other methods as soon as possible.

5.3 Conditional Uses in Floodway. The following uses and activities may be permitted as conditional uses, subject to the standards detailed in Sections 5.4:

5.31 Commercial extractive uses, and storage and stockpiling yards.

5.32 Structures accessory to uses detailed in Sections 5.11 and 5.31.

5.4 Standards for Conditional Uses in Floodway. In addition to the applicable standards detailed in Sections 4.0, 5.2 and 12.2:

5.41 Extractive uses and storage of materials require the completion of a site development and restoration plan, to be approved by the City of Delano.

5.42 Accessory Structures. Structures accessory to the uses detailed in Sections 5.11 and 5.31 must be constructed and placed so as to offer a minimal obstruction of flood waters and are subject to the standards in Section 6.23 of this ordinance.

SECTION 6.0 FF-1 FLOOD FRINGE DISTRICT ONE DISTRICT.

6.1 Permitted Uses in Flood Fringe One District. Any uses or activities allowed in any applicable underlying zoning districts may be allowed with a permit, subject to the standards set forth in Section 6.2.

6.2 Standards for Permitted Uses in FF-1 Flood Fringe One District. In addition to the applicable standards detailed in Section 4.0:

6.21 Residential Structures.

A. Elevation on Fill. Structures erected, constructed, reconstructed, altered, or moved on fill within the Flood Fringe District shall be placed so that the lowest floor, as defined in Section 2.0 of this ordinance, is elevated at or above the Regulatory Flood Protection Elevation (RFPE). The finished fill elevation shall be at

**City of Delano
County of Wright
State of Minnesota**


Ordinance O-24-05

or above the elevation associated with the base flood plus any stage increases that result from designation of a floodway.

B. Fill must extend at the same elevation at least 15 feet beyond the outside limits of the structure. Elevations must be certified by a registered professional engineer, land surveyor or other qualified person designated by the Zoning Administrator. Elevation methods alternative to these fill standards are subject to a Conditional Use Permit, as provided in Section 6.31 of this ordinance (Figure 2). Construction of this type shall only be permitted in locations where the natural ground is no lower than three feet below the base flood elevation.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05




Minnesota Department of Natural Resources Rev. 9.2021

Figure 2: Overview of fill standards for Residential Structures.

6.22 Nonresidential Principal Structures. Nonresidential principal structures must meet one of the following construction methods:

- A. Elevation on Fill. Structures may be elevated on fill, meeting the standards in Section 6.21.A of this ordinance. Fill for nonresidential structures is not required to be extended 15 feet beyond the outside limits of the structure.
- B. Alternative Elevation Methods. Structures may be elevated using methods alternative to the fill standards in Section 6.21.A of this ordinance. Such methods include the use of blocks, pilings (Figure 3), filled stem walls (Figure 4), or internally flooded enclosed areas (Figure 5) such as crawl spaces, attached garages, or tuck under garages.



City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

Figure 3: Blocks or pilings. Figure 4: Filled stem walls. Figure 4: Internally

C. Designs accommodating for internally flooded enclosed areas must be certified by a registered professional engineer or architect, or meet or exceed the standards detailed in *FEMA Technical Bulletin 1*, as amended, as well as the following standards:

- (1) The lowest floor, as defined in Section 2.0 of this ordinance, shall be elevated at or above the Regulatory Flood Protection Elevation (RFPE).
- (2) The floor of the enclosed area must be at or above the exterior grade on at least one side of the structure.
- (3) To allow for the equalization of hydrostatic pressure, there shall be a minimum of two openings below the base flood elevation on at least two sides of the structure. The bottom of all openings shall be no higher than one-foot above grade. The openings shall have a minimum net area of not less than one square inch for every square foot of enclosed area subject to flooding, have a net area of not less than one square inch for every square foot of enclosed area subject to flooding, and shall allow automatic entry and exit of floodwaters without human intervention.
- (4) Internally flooded enclosed areas shall only be used for the parking of vehicles, building access, or storage. Bathrooms and toilet rooms shall not be allowed. Such areas shall be subject to a deed-restricted non- conversion agreement as well as periodic inspections with the issuance of any permit.

D. Dry Floodproofing. Structures having watertight enclosed basements or spaces below the Regulatory Flood Protection Elevation (RFPE) must meet the following standards:

- (1) Walls must be substantially impermeable to the passage of water, with structural components having the capacity of resisting hydrostatic and hydrodynamic loads and effects of buoyancy, at least up to the Regulatory Flood Protection Elevation (RFPE).
- (2) Must meet the standards of *FEMA Technical Bulletin 3*, as amended; and
- (3) A registered professional engineer or architect shall be required to certify that the design and methods of construction meet the standards detailed in this Section.

6.23 Accessory Structures. All accessory structures must meet the following standards:

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

- A. Structures shall not be designed or used for human habitation.
- B. Structures will have a low flood damage potential.
- C. Structures with fewer than two rigid walls, such as carports, gazebos, and picnic pavilions, may be located at an elevation below the Regulatory Flood Protection Elevation.
- D. Structures with two or more rigid walls, must meet one of the following construction methods:
 - (1) Wet Floodproofing. Structures may be floodproofed in a way to accommodate internal flooding. Such structures shall constitute a minimal investment not to exceed 576 square feet in size, one-story in height, and shall only be used for parking and storage. To allow for the equalization of hydrostatic pressure, there shall be a minimum of two openings on at least two sides of the structure and the bottom of all openings shall be no higher than one-foot above grade. The openings shall have a minimum net area of not less than one square inch for every square foot of enclosed area subject to flooding and shall allow automatic entry and exit of floodwaters without human intervention.
 - (2) Elevation on Fill. Structures may be elevated on fill, meeting the standards in Section 6.21.A of this ordinance. Fill is not required to be extended 15 feet beyond the outside limits of the structure.
 - (3) Alternative Elevation Methods. Structures may have their lowest floor elevated above the Regulatory Flood Protection Elevation (RFPE) through methods alternative to the fill standards in Section 6.23.D(2) and must meet the standards in Section 6.22.B of this ordinance.
 - (4) Dry Floodproofing. Structures may be dry-floodproofed, or watertight, meeting the standards in Section 6.22.C of this ordinance.

6.24 All new principal structures must provide vehicular access no lower than one foot below the Base Flood Elevation (BFE), unless a flood warning/emergency evacuation plan has been approved by the City of Delano.

6.25 Any facilities used by employees or the general public must be designed with a flood warning system acceptable to the City of Delano that provides adequate time for evacuation, or be designed to ensure that within the area inundated during the base flood event, the depth (in feet) multiplied by the velocity (in feet per second) is less than four.

6.26 Manufactured homes and recreational vehicles must meet the standards of Section 11 of this ordinance.

6.3 **Conditional Uses in Flood Fringe.** The following uses and activities may be permitted as conditional uses, subject to the standards in Sections 6.4.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

6.31 Alternative Elevation Methods – Residential Structures. Residential structures with their lowest floor elevated above the Regulatory Flood Protection Elevation (RFPE) using methods alternative to the fill requirements in Section 6.21.

6.4 **Standards for Conditional Uses in Flood Fringe.** In addition to the applicable standards detailed in Sections 4.0, 6.2 and 12.2:

6.41 All residential structures with lowest floors elevated through alternative methods must meet the standards in Section 6.22.B and C of this ordinance.

SECTION 7.0 FF-2 FLOOD FRINGE DISTRICT TWO DISTRICT.

7.1 Permitted Uses in the Flood Fringe Two District: Permitted uses within the FF-2 shall be limited to the following:

7.11 General farming, pasture, grazing, forestry, sod farming and wild crop harvesting.

7.12 Industrial or commercial loading areas, parking areas, and airport landing strips

7.13 Private and public golf courses, tennis courts, driving ranges, archery ranges, picnic grounds, parks and open space, wildlife and nature preserves, game farms, shooting preserves, target ranges, trap and skeet ranges, hunting and fishing areas.

7.14 Residential lawns, gardens, parking areas and play areas.

7.15 Railroads, streets, bridges, utility transmission lines and pipelines pursuant to Section 10.0 of this ordinance.

7.16 Stormwater management practices including the construction of ponding or drainage ways.

7.2 Standards for Permitted Uses in FF-2 Flood Fringe Two District. In addition to the applicable standards detailed in Section 4.0: All permitted uses shall comply with the standards for Flood Fringe District Two "Permitted Uses" listed in Section 7.1 and the standards for all Flood Fringe District Two "Permitted and Conditional Uses" listed in Section 6.4.

7.21 The use shall have a low flood damage potential.

7.22 Buildings for human habitation shall be prohibited.

7.23 The use shall not obstruct flood flows or increase flood elevations.

7.24 All lots in a subdivision within a floodplain approved after January 1, 2006, shall meet the minimum lot area standards of the underlying zoning district exclusive of land identified as flood fringe, as identified in the Flood Insurance Rate Map adopted in Section 3.2 of this Ordinance.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

7.3 Conditional Uses: An application for a conditional use shall be subject to the standards and criteria and evaluation procedures specified in Sections 7.4, 7.5. 8.0 and 12.2 of this Ordinance. The following are conditional uses permitted in the FF-2 District:

7.31 Essential service structures necessary for the health, safety and general welfare of the City, pursuant to Section 10.0 of this Ordinance.

7.32 Structures accessory to the uses listed in Section 7.1.

7.23 Extraction and storage of sand, gravel and other materials.

7.4 Standards for FF-2 District Conditional Uses:

7.41 Accessory structures shall not be designed for human habitation.

7.42 All structures, including basements, to be placed below the Regulatory Flood Protection Elevation shall be flood proofed in accordance with the following standards: Walls must be substantially impermeable to the passage of water, with structural components having the capacity of resisting hydrostatic and hydrodynamic loads and effects of buoyancy, at least up to the Regulatory Flood Protection Elevation (RFPE); must meet the standards of FEMA Technical Bulletin 3, as amended; and a registered professional engineer or architect shall be required to certify that the design and methods of construction meet the standards detailed in this Section.

7.43 When at any one time more than one thousand (1,000) cubic yards of fill or other similar material is located on a parcel for such activities as on-site storage, landscaping, sand and gravel operations, landfills, roads, dredge spoil disposal or construction of flood control works, an erosion/sedimentation control plan must be submitted. The plan must clearly specify methods to be used to stabilize the fill on site for a flood event at a minimum of the 100-year or regional flood event. The plan must be prepared and certified by a registered professional engineer or other qualified individual acceptable to the City. The plan may incorporate alternative procedures for removal of the material from the floodplain if adequate flood warning time exists.

7.44 Storage of Materials and Equipment: (1) The storage of materials that are, in time of flooding, flammable, explosive, or potentially injurious to human, animal, or plant life is prohibited. (2) Storage of other materials or equipment may be allowed if readily removable from the area within the time available after a flood warning and in accordance with a plan approved by the City.

7.45 All FF-2 District Conditional Uses shall be subject to the procedures and standards contained in Section 12.2 of this Ordinance.

7.46 The Conditional use shall be permissible in the underlying zoning district, if one exists.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

7.5 Standards for All FF-2 District Uses:

7.51 Fill shall be properly compacted, and the slopes shall be properly protected by the use of riprap, vegetative cover or other acceptable method. The Federal Emergency Management Agency (FEMA) has established criteria for removing the special flood hazard area designation for certain structures properly elevated on fill above the 100-year flood elevation - FEMA's requirements incorporate specific fill compaction and side slope protection standards for multistucture or multi-lot developments. These standards should be investigated prior to the initiation of site preparation if a change of special flood hazards area designations is requested.

7.52 Floodplain developments shall not adversely affect the hydraulic capacity of the channel and adjoining floodplain of any tributary watercourse or drainage system where a floodway or other encroachment limit has not been specified on the Official Zoning Map.

SECTION 8.0 General Floodplain District

8.1 Permitted Uses in General Floodplain District

8.11 Until the floodway is delineated, allowable uses will be restricted to those listed in the Floodway District, Section 5.0.

8.12 All other uses are subject to a floodway/flood fringe determination as provided in Section 8.4, in addition to the standards provided in Sections 8.2 and 8.3. Permitted uses shall be determined as follows:

- A. If the development is determined to be in the Floodway District, Section 5.0 applies.
- B. If the development is determined to be in the Flood Fringe One District or Flood Fringe Two District, Sections 6.0 or 7.0 applies.

8.2 Determining Flood Elevations

8.21 All development requires a determination of the Base Flood Elevation (BFE). Exceptions to this requirement include projects that restore the site to the previous cross-sectional area, such as shore stabilization or culvert replacement projects. Base Flood Elevations (BFE) may be found using best available data from any Federal, State, or other source (including MNDNR's Lake & Flood Elevations Online (LFEO) Viewer).

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

8.22 The Regulatory Flood Protection Elevation (RFPE) can be determined by assuming a one-half (0.5) foot stage increase to accommodate for future cumulative impacts. A stage increase does not need to be assumed along lakes, wetlands, and other basins that are not affected by velocities.

8.3 Encroachment Analysis

8.31 Encroachments due to development may not allow stage increases more than one-half (0.5) foot at any point, unless through a map revision following the procedures in Sections 12.15 and 15.0. This evaluation must include the cumulative effects of previous encroachments and must be documented with hydrologic and hydraulic analysis performed by a professional engineer or using other standard engineering practices. A lesser water surface elevation increase than one-half (0.5) foot is required if, due to the water surface level increase, increased flood damage would potentially result.

8.32 Alterations or changes that result in stage decreases are allowed and encouraged.

8.4 Standards for the Analysis of Floodway Boundaries

8.41 Requirements for Detailed Studies. Any development, as requested by the Zoning Administrator, shall be subject to a detailed study to determine the Regulatory Flood Protection Elevation (RFPE) and the limits of the Floodway District. This determination must be consistent with the minimum standards for hydrologic and hydraulic mapping standards and techniques, as detailed in Minnesota Rules, part 6120.5600, Subp. 4 and *FEMA Guidelines and Standards for Flood Risk Analysis and Mapping*, as revised. Additionally:

- A. A regulatory floodway necessary to carry the discharge of the one-percent annual chance flood must be selected without increasing the water surface elevation more than one-half (0.5) foot at any point. This determination should include the cumulative effects of previous encroachments. A lesser water surface elevation increase than one-half (0.5) foot is required if, due to the water surface level increase, increased flood damages would potentially result; and
- B. An equal degree of encroachment on both sides of the stream within the reach must be assumed in computing floodway boundaries, unless topography, existing development patterns, and comprehensive land use plans justify a modified approach, as approved by the Department of Natural Resources.

8.42 Other Acceptable Methods. For areas where a detailed study is not available or required:

- A. Development prohibited in floodways (e.g. most buildings) requires a floodway/flood fringe determination to verify the development is within the flood fringe. This determination must be done by a professional engineer or utilize other accepted engineering practices. The

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

Department of Natural Resources may also provide technical assistance and must approve any alternative methods used to determine floodway boundaries.

B. For areas where the floodway has not been determined in and along lakes, wetlands, and other basins, the following methodology may be used as an alternative to Item A above, provided these areas are not affected by velocities and the lot is able to accommodate a building site above the Regulatory Flood Protection Elevation (RFPE):

- (1) All areas that are at or below the ordinary high water level, as defined in Minnesota Statutes, section 103G.005, Subd. 14, will be considered floodway, and all areas below the Base Flood Elevation (BFE) but above the ordinary high water level will be considered flood fringe, provided that within 25 feet of the ordinary high water level, or within the Shore Impact Zone as identified in the community's Shoreland ordinance, whichever is greater, land alterations shall be restricted to:
 - a. The minimum required to accommodate beach areas, access areas, and accessory structures as permitted, not to exceed a volume greater than 10 cubic yards; projects involving volumes exceeding 10 cubic yards require floodway/flood fringe determination in accordance with the procedures in Section 8.4, item A; and
 - b. The minimum required to accommodate shoreline stabilization projects to correct an identified erosion problem as verified by a qualified resource agency or the zoning administrator.

9.0 SUBDIVISION STANDARDS

9.1 Subdivisions. All subdivided land must meet the following requirements. Manufactured home parks and recreational vehicle parks or campgrounds are considered subdivisions under this ordinance.

9.11 All lots within floodplain districts must be suitable for a building site outside of the Floodway District and the FF-2 Flood Fringe Two District.

9.12 Subdivision of lands within the floodplain districts may not be approved if the cost of providing governmental services would impose an unreasonable economic burden on the City of Delano.

9.13 All subdivisions must have vehicular access both to the subdivision and to the individual building sites no lower than two feet below the Regulatory Flood Protection Elevation (RFPE), unless a flood warning/emergency evacuation plan has been approved by the City of Delano.

9.14 The Floodway and Flood Fringe District boundaries, the Regulatory Flood Protection Elevation (RFPE) and the required elevation of all access roads must be clearly identified on all required subdivision drawings and platting documents.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

SECTION 10.0 PUBLIC AND PRIVATE UTILITIES, SERVICE FACILITES, ROADS, BRIDGES, AND RAILROADS

10.1 Public Transportation Facilities. Railroad tracks, roads, and bridges must be elevated to the Regulatory Flood Protection Elevation (RFPE) where such facilities are essential to the orderly functioning of the area, or where failure or interruption would result in danger to public health or safety. Minor or auxiliary roads or railroads may be constructed at a lower elevation where failure or interruption of transportation services would not endanger the public health or safety. All public transportation facilities should be designed to minimize increases in flood elevations.

10.2 Public Utilities. All utilities such as gas, electrical, sewer, and water supply systems to be located in the floodplain must be elevated and/or floodproofed to the Regulatory Flood Protection Elevation (RFPE), be located and constructed to minimize or eliminate flood damage and be designed to eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters. All public utilities should be designed to minimize increases in flood elevations. New solid waste management facilities, as defined in Minnesota Rules, part 7035.0300, are prohibited in the one-percent annual chance floodplain. Water supply systems are subject to the provisions in Minnesota Rules, part 4725.4350.

10.3 Private On-Site Water Supply, Individual Sewage Treatment Systems, and other Service Facilities. Private facilities shall be subject to applicable provisions detailed in Section 10.2. In addition, new or replacement on-site sewage treatment systems are to be located to avoid impairment to them or contamination from them during times of flooding, shall not be located in a designated floodway, and are subject to the provisions in Minnesota Rules, parts 7080.2270.

SECTION 11 MANUFACTURED HOMES AND RECREATIONAL VEHICLES

11.1 Manufactured Homes. Manufactured homes and manufactured home parks are subject to applicable standards for each floodplain district. In addition:

11.11 New and replacement manufactured homes must be placed and elevated in compliance with Section 6.0 of this ordinance and must be securely anchored to a system that resists flotation, collapse and lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors.

11.22 New manufactured home parks and expansions to existing manufactured home parks must meet the appropriate standards for subdivisions in Section 9.0 of this ordinance.

11.2 Recreational Vehicles. New recreational vehicle parks or campgrounds and expansions to existing recreational vehicle parks or campgrounds are prohibited in any floodplain district. Recreational

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

vehicles placed in existing recreational vehicle parks, campgrounds or lots of record in the floodplain must either:

11.21 Meet the requirements for manufactured homes in Section 11.1, or

11.22 Be travel ready, meeting the following criteria:

- A. The vehicle must be fully licensed.
- B. The vehicle must be ready for highway use, meaning on wheels or the internal jacking system, attached to the site only by quick disconnect type utilities.
- C. No permanent structural type additions may be attached to the vehicle.
- D. Accessory structures may be permitted in the Flood Fringe District, provided they do not hinder the removal of the vehicle should flooding occur, and meet the standards outlined in Sections 4.0 and 6.23.

SECTION 12.0 ADMINISTRATION

12.1 **Duties.** A Zoning Administrator or other official must administer and enforce this ordinance.

12.11 **Permit Application Requirements.** Permit applications must be submitted to the Zoning Administrator. The permit application must include the following, as applicable:

- A. A site plan showing all existing or proposed buildings, structures, service facilities, potential obstructions, and pertinent design features having an influence on the permit.
- B. Location and detail of grading, fill, or storage of materials.
- C. Copies of any required local, state or federal permits or approvals.
- D. Other relevant information requested by the Zoning Administrator as necessary to properly evaluate the permit application.

12.12 **Recordkeeping.** The Zoning Administrator must maintain applicable records in perpetuity documenting:

- A. All certifications for dry floodproofing and alternative elevation methods, where applicable.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

- B. Analysis of no-rise in the Floodway District, as detailed in Section 5.21, and encroachment analysis ensuring no more than one-half foot of rise in the General Floodplain District, as detailed in Sections 8.22 and 8.31.
- C. Final elevations, as applicable, detailing the elevation to which structures and improvements to structures are constructed or floodproofed. Elevations shall be determined by an engineer, architect, surveyor or other qualified individual, as approved by the Zoning Administrator.
- D. Substantial damage and substantial improvement determinations, as detailed in Section 13.13, including the cost of improvements, repairs, and market value.
- E. All variance actions, including justification for their issuance, and must report such variances as requested by the Federal Emergency Management Agency.

12.13 Certificate of Zoning Compliance for a New, Altered, or Nonconforming Use. No building, land or structure may be occupied or used in any manner until a certificate of zoning compliance has been issued by the Zoning Administrator stating that the finished fill and building floor elevations or other flood protection measures are in compliance with the requirements of this ordinance.

12.14 Notifications for Watercourse Alterations. Before authorizing any alteration or relocation of a river or stream, the Zoning Administrator must notify adjacent communities. If the applicant has applied for a permit to work in public waters in accordance with Minnesota Statutes, Section 103G.245, this will suffice as adequate notice. A copy of the notification must also be submitted to FEMA.

12.15 Notification to FEMA When Physical Changes Increase or Decrease Base Flood Elevations. Where physical changes affecting flooding conditions may increase or decrease the water surface elevation of the base flood, the City of Delano must notify FEMA of the changes in order to obtain a Letter of Map Revision (LOMR), by submitting a copy of the relevant technical or scientific data as soon as practicable, but no later than six months after the date such supporting information becomes available. Within the General Floodplain District, a map revision is only required if development results in stage increases greater than 0.5 feet.

12.2 Conditional Uses and Variances

12.21 Process.

- A. An application for a conditional use permit will be processed and reviewed in accordance with the provisions of this ordinance.

**City of Delano
County of Wright
State of Minnesota**

Ordinance O-24-05

B. An application for a variance to the provisions of this ordinance will be processed and reviewed in accordance with Minnesota Statutes, section 462.357, Subd. 6(2) and this ordinance.

12.22 Additional Variance Criteria. The following additional variance criteria must be satisfied:

- A. Variances must not be issued within any designated regulatory floodway if any increase in flood levels during the base flood discharge would result.
- B. Variances from the provisions of this ordinance may only be issued by a community upon:
 - (1) A showing of good and sufficient cause.
 - (2) A determination that failure to grant the variance would result in exceptional hardship to the applicant; and
 - (3) A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- C. Variances from the provisions in this ordinance may only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
- D. Variances must be consistent with the general purpose of these standards and the intent of applicable provisions in state and federal law.
- E. Variances may be used to modify permissible methods of flood protection, but no variance shall permit a lesser degree of flood protection than the Regulatory Flood Protection Elevation (RFPE).
- F. The Zoning Administrator must notify the applicant for a variance in writing that:
 - (1) The issuance of a variance to construct a structure below the base flood level will result in increased premium rates for flood insurance up to amounts as high as \$25 for \$100 of insurance coverage; and
 - (2) Such construction below the base flood level increases risks to life and property. Notification must be maintained with a record of all variance actions.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

12.23 Considerations for Approval. The City of Delano must consider all relevant factors specified in other sections of this ordinance in granting variances and conditional use permits, including the following:

- A. The potential danger to life and property due to increased flood heights or velocities caused by encroachments.
- B. The danger that materials may be swept onto other lands or downstream to the injury of others.
- C. The safety of access to the property in times of flood for ordinary and emergency vehicles.

12.24 Conditions of Approval. The City of Delano may attach such conditions to the granting of variances and conditional use permits as it deems necessary to fulfill the purposes of this ordinance. Such conditions may include, but are not limited to, the following:

- A. Limitations on period of use, occupancy, and operation.
- B. Imposition of operational controls, sureties, and deed restrictions.
- C. The prevention of soil erosion or other possible pollution of public waters, both during and after construction.
- D. Other conditions as deemed appropriate by the Zoning Administrator and/or City Council.

12.3 Notifications to the Department of Natural Resources

12.31 All notices of public hearings to consider variances or conditional uses under this ordinance must be sent via electronic mail to the Department of Natural Resources respective area hydrologist at least ten (10) days before the hearings. Notices of hearings to consider subdivisions/plats must include copies of the subdivision/plat.

12.32 A copy of all decisions granting variances and conditional uses under this ordinance must be sent via electronic mail to the Department of Natural Resources respective area hydrologist within ten (10) days of final action.

SECTION 13.0 NONCONFORMITIES

13.1 Continuance of Nonconformities. A use, structure, or occupancy of land which was lawful before the passage or amendment of this ordinance, but which is not in conformity with the provisions of this ordinance, may be continued subject to the following conditions:

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

13.11 Within the floodway and general floodplain districts (when a site has been determined to be located in the floodway following the procedures in Section 8.3, or when the floodway has not been delineated), any expansion or enlargement of uses or structures is prohibited.

13.12 Within all districts, any addition, modification, rehabilitation, repair, or alteration shall be in conformance with the provisions of this ordinance, shall not increase the flood damage potential or increase the degree of obstruction to flood flows, and where applicable, must be protected to the Regulatory Flood Protection Elevation (RFPE).

13.13 If any nonconforming structure is determined to be substantially damaged or substantially improved based on the procedures in Section 13.2, it may not be reconstructed except in conformity with the provisions of this ordinance. Any structures located outside the one-percent annual chance floodplain are exempt from this provision.

13.14 If any nonconforming use, or any use of a nonconforming structure, is discontinued for more than one year, any future use of the premises must conform to this ordinance.

13.15 If any nonconforming structure has utilities, electrical, or mechanical equipment damaged due to flooding, it must be rebuilt in conformance with the elevation requirements in Section 4.31.D to the greatest extent practicable. This requirement shall apply regardless of the determinations made in Section 13.2.

13.2 Substantial Improvement and Substantial Damage Determinations. Prior to issuing any permits for additions, modifications, rehabilitations, repairs, alterations, or maintenance to nonconforming structures, the Zoning Administrator is required to determine if such work constitutes substantial improvement or repair of a substantially damaged structure. A determination must be made in accordance with the following procedures:

13.21 Estimate the market value of the structure. In the case of repairs, the market value of the structure shall be the market value before the damage occurred and before any restoration or repairs are made.

13.22 Estimate the cost of the project. The property owner shall accommodate for inspection, and furnish other documentation needed by the zoning administrator to evaluate costs.

- A. Improvement costs shall be comprised of the market rate of all materials and labor, as well as the costs of all ordinary maintenance and upkeep carried out over the past one year.
- B. Costs to repair damages shall be comprised of the market rate of all materials and labor required to restore a building to its pre-damaged condition regardless of the

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

work proposed, as well as associated improvement costs if structure is being restored beyond its pre-damaged condition.

13.23 Compare the cost of the improvement, repairs, or combination thereof to the estimated market value of the structure and determine whether the proposed work constitutes substantial improvement or repair of a substantially damaged structure, as defined in Section 2.0 of this ordinance.

- A. For the purposes of determining whether the proposed work would constitute substantial improvement, the evaluation shall also include all improvements completed since the community has adopted floodplain standards impacting this structure.
- B. If any nonconforming structure experiences a repetitive loss, as defined in Section 2.0 of this ordinance, it shall be considered substantially damaged and must not be reconstructed except in conformity with the provisions of this ordinance.

13.24 Based on this determination, the zoning administrator shall prepare a determination letter and notify the property owner accordingly. Structures determined to be substantially damaged or substantially improved may not be reconstructed except in conformity with the provisions of this ordinance.

SECTION 14.0 VIOLATIONS AND PENALTIES

14.1 Uses in Violation of the Ordinance. Every structure, fill, deposit, or other use placed or maintained in the floodplain in violation of this ordinance shall be considered a public nuisance.

14.2 Civil Remedies. The creation of a public nuisance may be enjoined and the maintenance of a public nuisance under this ordinance may be abated by an action brought by the City of Delano or the Department of Natural Resources.

14.3 Enforcement. Violations of the provisions of this ordinance constitute a misdemeanor and is punishable as defined by law. The Zoning Administrator may utilize the full array of enforcement actions available to it including but not limited to prosecution and fines, injunctions, after-the-fact permits, orders for corrective measures or a request to the National Flood Insurance Program for denial of flood insurance. The City of Delano must act in good faith to enforce these official controls and to correct ordinance violations to the extent possible so as not to jeopardize its eligibility in the National Flood Insurance Program.

City of Delano
County of Wright
State of Minnesota

Ordinance O-24-05

SECTION 15.0 AMENDMENTS

15.1 Ordinance Amendments. Any revisions to the floodplain maps by the Federal Emergency Management Agency or annexations of new map panels require an ordinance amendment to update the map references in Section 3.2 of this ordinance.

15.2 Required Approval. All amendments to this ordinance must be submitted to the Department of Natural Resources for review and approval prior to adoption, for compliance with state and federal rules and requirements. The floodplain ordinance shall not be considered valid until approved.

EFFECTIVE DATE: This ordinance shall be in full force and effect from and after its passage and approval.

Adopted by the City Council of the City of Delano, Minnesota on June 18, 2024.

Signed:

Holly Schrupp, Mayor

Attest: Paula Bauman, City Clerk